

# KIMA Dark Red 18

## Application:


Thin floor construction on top of an existing concrete floor construction in wet and dry areas.

Ordinary concrete constructions in wet and dry areas.



## Produktfakta:

- Flameretardent twin conductor
- Metallic Sheat, 100% coverage
- Type 12-4
- Insulation class I
- IP67
- Max operating temperature +70°C
- Min installation temperature -15°C
- Voltage 230 Volt
- Wattage 18 W/m
- Diameter 4,50 mm
- 2 m coldtail with earth
- Manufactured according to standard EN60800
- Complies with RoHS directive



120 W/m <sup>2</sup>	= c/c 15 cm
100 W/m <sup>2</sup>	= c/c 18 cm
85 W/m <sup>2</sup>	= c/c 21 cm
75 W/m <sup>2</sup>	= c/c 24 cm
60 W/m <sup>2</sup>	= c/c 30 cm
50 W/m <sup>2</sup>	= c/c 36 cm

Part no.	EAN no.	Product Type	Length (m)	Wattage (W)	Tolerance total (Ohm)	I (Amp)
125 000 65	7331002913467	KIMA Dark Red	6,5	120	419 - 485	0,6
125 001 00	7331002913474	KIMA Dark Red	10	175	287 - 333	0,8
125 001 30	7331002913481	KIMA Dark Red	13	230	219 - 253	1,0
125 001 60	7331002913498	KIMA Dark Red	16	300	168 - 194	1,3
125 002 30	7331002913504	KIMA Dark Red	23	400	126 - 145	1,8
125 002 90	7331002913511	KIMA Dark Red	29	525	96 - 111	2,3
125 003 90	7331002913528	KIMA Dark Red	39	700	72 - 83	3,0
125 004 70	7331002913535	KIMA Dark Red	47	850	59 - 68	3,7
125 005 20	7331002913542	KIMA Dark Red	52	930	54 - 63	4,0
125 006 00	7331002913559	KIMA Dark Red	60	1075	47 - 54	4,7
125 007 00	7331002913566	KIMA Dark Red	70	1200	42 - 48	5,2
125 007 50	7331002913573	KIMA Dark Red	75	1350	37 - 43	5,8
125 009 00	7331002913580	KIMA Dark Red	90	1550	32 - 38	6,8
125 010 50	7331002913597	KIMA Dark Red	105	1900	26 - 31	8,3
125 012 00	7331002913603	KIMA Dark Red	120	2150	23 - 27	9,4
125 013 50	7331002913610	KIMA Dark Red	135	2450	21 - 24	10,7
125 015 50	7331002913627	KIMA Dark Red	155	2750	18 - 21	12,0
125 016 50	7331002913634	KIMA Dark Red	165	3000	17 - 19	13,0
125 017 50	7331002913641	KIMA Dark Red	175	3200	16 - 18	14,0
125 019 50	7331002913658	KIMA Dark Red	195	3500	14 - 17	15,3

PRO00101029 141120