



Kima K4

Application:


Snow and ice melting roof and gutters.
Frost protection pipes outside
diameter > 200 mm, installation on the pipe.

Specification:

- Flameretardent selflimiting heatingcable.
- Steel armoured metallic sheath with minimum electric fields.
- Insulation class I.
- IP67.
- Operating temperature max +65°C.
- Tappwarmwater should never be higher than +55°C and the selflimiting heating cable should only be energized when there is a risk for freezing, pipe temperature lower than +5°C. The selflimiting heating cable should be regulated by a thermostat and the sensor installed on the pipe.
- Mecanical strength; armoured class C according to EN60800.
- Voltage 230 Volt.
- Wattage 28 W/m vid + 5°C.
- 170 mAmp current operation at -10°C.
- Manufactured according to standard EN60800, SS4242411.
- Complies with RoHS directiv 2002/95/EC.



Nominell poweroutput K4 at different cable temperatures



Part no.	EAN no.	Product Type	Length (m)	Wattage (W/m)
20090016	7331002911272	KIMA K4	Supplied on reel	28

Tillbehör

Part no.	EAN no.	Product Type
E 89 876 57	7331002908111	KIMA K2/K3/K4 Connection Kit
E 89 876 58	7331002908128	KIMA K2/K3/K4 End Seal Kit
E 89 876 59	7331002908135	KIMA K2/K3/K4 Splice Kit Cold Tail
E 89 876 55	7331002908104	KIMA K2/K3/K4 Connection & End Seal Kit

Electricfuse Amp	Max Cable Length m
10	40

Min temperature for energizing the selflimiting heating cable is -15°C

