

# Kima Warm Floor Mat Kit



## Application:

Thin floor construction on top of an existing concrete floor construction in wet and dry areas. Ordinary concrete constructions in wet and dry areas.

**Important! The heating cable can not be cut.**

## Product content:

- Underfloor Heatingmat
- Thermostat, E 85 811 37
- Floor sensor tube

## Specification:

- Kima Warm Floor Mat 120.
- Kima Zone 30.



Part no.	EAN no.	Product Type	Width (mm)	Length (m)	Wattage (W)	Area (m <sup>2</sup> )	Tolerance total (Ohm)
E 89 878 47	7331002905141	KIMA WFMK 120	500	1,9	110	0,95	457 - 529
E 89 878 51	7331002905158	KIMA WFMK 120	500	3,2	190	1,6	265 - 306
E 89 878 52	7331002905165	KIMA WFMK 120	500	4,0	240	2,0	209 - 242
E 89 878 48	7331002905172	KIMA WFMK 120	500	4,8	285	2,4	176 - 204
E 89 878 53	7331002905189	KIMA WFMK 120	500	6,2	390	3,1	129 - 149
E 89 878 49	7331002905196	KIMA WFMK 120	500	7,2	430	3,6	117 - 135
E 89 878 54	7331002905202	KIMA WFMK 120	500	8,0	470	4,0	107 - 124
E 89 878 55	7331002905219	KIMA WFMK 120	500	10,2	635	5,1	79 - 92
E 89 878 56	7331002905226	KIMA WFMK 120	500	12,6	760	6,3	66 - 77
E 89 878 57	7331002905233	KIMA WFMK 120	500	14,8	880	7,4	57 - 66
E 89 878 58	7331002905240	KIMA WFMK 120	500	17,0	975	8,5	52 - 60
E 89 878 60	7331002905257	KIMA WFMK 120	500	21,0	1300	10,5	39 - 45
E 89 878 63	7331002905264	KIMA WFMK 120	500	26,0	1550	13,0	32 - 38